

# CONTROLLED COPY CENTRAL FILE

## THREE MILE ISLAND NUCLEAR STATION UNIT #2 OPERATING PROCEDURE 2106-2.2 CONDENSATE POLISHING SYSTEM

APR 23 1979

2106-2.2  
Revision 9  
03/21/79

Table of Effective Pages

Page	Date	Revision	Page	Date	Revision	Page	Date	Revision
1.0	03/21/79	9	26.0	03/21/79	9	51.0	03/21/79	9
2.0	09/26/77	2	27.0	03/21/79	9	52.0	03/21/79	9
3.0	12/15/78	8	28.0	03/21/79	9	53.0	03/21/79	9
4.0	03/21/79	9	29.0	03/21/79	9	54.0	03/21/79	9
5.0	03/21/79	9	30.0	03/21/79	9	55.0	03/21/79	9
6.0	03/21/79	9	31.0	03/21/79	9	56.0	03/21/79	9
7.0	03/21/79	9	32.0	03/21/79	9	57.0	03/21/79	9
8.0	03/21/79	9	33.0	03/21/79	9	58.0	03/21/79	9
9.0	03/21/79	9	34.0	03/21/79	9	59.0	03/21/79	9
10.0	03/21/79	9	35.0	03/21/79	9	60.0	03/21/79	9
11.0	03/21/79	9	36.0	03/21/79	9	61.0	03/21/79	9
12.0	03/21/79	9	37.0	03/21/79	9	62.0	03/21/79	9
13.0	03/21/79	9	38.0	03/21/79	9	63.0	03/21/79	9
14.0	03/21/79	9	39.0	03/21/79	9	64.0		
15.0	03/21/79	9	40.0	03/21/79	9	65.0		
16.0	03/21/79	9	41.0	03/21/79	9	66.0		
17.0	03/21/79	9	42.0	03/21/79	9	67.0		
18.0	03/21/79	9	43.0	03/21/79	9	68.0		
19.0	03/21/79	9	44.0	03/21/79	9	69.0		
20.0	03/21/79	9	45.0	03/21/79	9	70.0		
21.0	03/21/79	9	46.0	03/21/79	9	71.0		
22.0	03/21/79	9	47.0	03/21/79	9	72.0		
23.0	03/21/79	9	48.0	03/21/79	9	73.0		
24.0	03/21/79	9	49.0	03/21/79	9	74.0		
25.0	03/21/79	9	50.0	03/21/79	9	75.0		

Unit 1 Staff Recommends Approval

Approval N/A Date \_\_\_\_\_  
Cognizant Dept. Head

Unit 2 Staff Recommends Approval

Approval [Signature] Date 3/21/79  
Cognizant Dept. Head

Unit 1 PORC Recommends Approval

N/A Date \_\_\_\_\_  
Chairman of PORC

Unit 2 PORC Recommends Approval

N/A Date \_\_\_\_\_  
Chairman of PORC

Unit 1 Superintendent Approval

N/A Date \_\_\_\_\_

Unit 2 Superintendent Approval

[Signature] Date 3/21/79

Manager Generation Quality Assurance Approval N/A Date \_\_\_\_\_

THREE MILE ISLAND NUCLEAR STATION  
 UNIT #2 OPERATING PROCEDURE 2106-2.2  
 CONDENSATE POLISHING SYSTEM  
2106-2.2A Table of Contents

<u>Section</u>	<u>Page</u>
1.0 <u>REFERENCES</u>	2.0
1.1 Drawings Applicable for Operation	2.0
1.2 Operating Procedures Applicable for Operation	2.0
1.3 Manufacturers' Instruction Manuals	2.0
1.4 Applicable System Descriptions	2.0
1.5 Curves, Tables, etc.	3.0
2.0 <u>LIMITS AND PRECAUTIONS</u>	3.0
2.1 Equipment	3.0
2.2 Administrative	3.0
3.0 <u>PREREQUISITES</u>	4.0
4.0 <u>PROCEDURE</u>	4.0
4.1 Start-Up	4.0
4.2 Normal Operation	5.0
4.3 Shutdown	6.0
4.4 Loading Aqueous Ammonia	6.0

APPENDIX

<u>Title</u>	<u>No.</u>	
Valve Line-up	A	7.0
Valve Line-up Signature Sheet	B	25.0
Short Regeneration	C	62.0
Mini-Ammonex	D	63.0

194 219

CCS  
APR 23 1979

2106-2.2  
Revision 2  
09/26/77

THREE MILE ISLAND NUCLEAR STATION  
UNIT #2 OPERATING PROCEDURE 2106-2.2

CONDENSATE POLISHING SYSTEM

2106-2.2A

1.0 REFERENCES

1.1 Drawings Applicable for Operation.

- 1.1.1 Make-Up Water Treatment and Condensate Polishing, B&R Dwg. 2006.
- 1.1.2 Condensate Demineralizer Mixed Bed Polisher System, L\*A Water Conditioning Co. Dwg. 015-00-0405.
- 1.1.3 Condensate Demineralizer External Regen. System, L\*A Water Conditioning Co. Dwg. 015-00-0406.

1.2 Operating Procedures Applicable for Operation.

- 1.2.1 2102-1.1 Unit Heat-Up.
- 1.2.2 2104-2.1 Cycle Make-Up Pretreatment.
- 1.2.3 2104-2.2 Demineralized Service Water.
- 1.2.4 2104-2.3 Instrument Air.
- 1.2.5 2104-2.8 Secondary Plant Sampling.
- 1.2.6 2104-2.9 Demineralizing System.
- 1.2.7 2106-2.1 Condensate.
- 1.2.8 2106-2.4 Feedwater.
- 1.2.9 2107-1.1 BOP Electrical.

1.3 Manufacturers Instruction Manuals.

- 1.3.1 L\*A Water Purification System, Volumes I thru V B&R File # (15.00).

1.4 Applicable System Descriptions.

- 1.4.1 Feedwater and Condensate, Index No. 4A.



APR 23 1979

2106-2.2  
Revision 8  
12/15/78

- 1.4.2 Condensate Polishing, Index No. 4B.
- 1.4.3 Make-Up Water Treatment, Index No. 4C.
- 1.4.4 Secondary Plant Sampling, Index No. 12.
- 1.5 Curves, Tables, etc.
- 1.5.1 Table 1A, Service and Resin Transfer In - Remote Manual Operation.
- 2.0 LIMITS AND PRECAUTIONS
- 2.1 Equipment
  - 2.1.1 Remove a polisher from service when an alarm annunciates high pressure drop across the resin trap, and ensure there has been no resin loss due to underdrain screen break. (Max.  $\Delta P$  5# across resin trap and Max.  $\Delta P$  40# across polisher at full flow.)
- 2.2 Administrative.
  - 2.2.1 The Condensate Polishing System demineralizes feedwater which potentially contains radioactive material should a Primary to Secondary Leak exist. Since these radioactive materials would be concentrated in the mixed bed resin, the resin should be treated as potentially radioactive under this condition.
  - 2.2.2 A polishing tank should be rinsed to drain for 5 minutes when initially placed in service to prevent contamination of feedwater.
  - 2.2.3 A polishing tank should be taken out of service, and the exhausted resin regenerated, when an alarm annunciates polisher high effluent conductivity or gallonage exhaustion. This is necessary to prevent contamination of feedwater.
  - 2.2.4 Ensure the heat tracing on the system components and piping is energized for both freeze protection and to prevent chemical crystallization.



CCJ  
APR 23 1979

2106-2.2  
Revision 9  
03/21/79

- 2.2.5 Observe safety precautions for strong chemicals when working with ammonium hydrozide, hydrazine, acid and caustic.
- 2.2.6 100% condensate flow must pass thru condensate polishing demineralizers prior to feeding OTSG's. If evidence of condenser tube leakage is observed, MSR drains will be routed directly to the Hot Well which will increase the rate of resin exhaustion in condensate polishing demineralizers.
- 2.2.7 While polishers are in service the local air switches for the inlet valves, inlet bypass valves and outlet valves should be placed in the OPEN position. When a polisher is removed from service or is in standby, the local air switches for these valves should be in AUTO.

### 3.0 PREREQUISITES

Initial Each Step

- \_\_\_ 3.1 Electrical power available (2107-1.1).

<u>Component</u>	<u>Source</u>	<u>Unit</u>
WT-P-19A	2-31A	10A
WT-P-19B	2-41A	7B

- \_\_\_ 3.2 Instrument air is in operation per 21042.3.

- \_\_\_ 3.3 Condensate polishing tanks filled with regenerated mixed bed resin.

- \_\_\_ 3.4 Valve line-up complete Appendix A.

- \_\_\_ 3.5 Service Air in operation per 2104-2.10.

- \_\_\_ 3.6 Demineralized water available 2104-2.2.

### 4.0 PROCEDURE

Initial Each Step.

194 222

CCJ  
APR 23 1979

2106-2.2  
Revision 9  
03/21/79

#### 4.1 Start-up.

\_\_\_\_ 4.1.1 Place the local control switches for the condensate polisher regeneration sump pumps in AUTO.

\_\_\_\_ 4.1.2 When a condensate pump is started, vent the polishing tanks as necessary by opening and then closing vent valves M13, M23, M33, M43, M53, M63, M73 and M83.

CAUTION: Exercise care not to force resin out of vent as vents are not screened.

\_\_\_\_ 4.1.3 After all polisher tanks are properly vented, CLOSE the EFFLUENT and INFLUENT valves for the polisher tank selected as standby.

\_\_\_\_ 4.1.4 Shut CO-V12 and adjust the effluent valve positions of the in-service polishers to achieve equal flow through each tank as indicated on the Panel 304 flow recorders.

NOTE: Start-up recirculation back to the condenser will be provided by the Feedwater System normal startup valve line-up.

#### 4.2 Normal Operation.

Monitor system parameters as necessary to insure proper operation. Periodically check all components in the Condensate Polishing System.

##### 4.2.1 Shifting Polishers To and From Service.

NOTE: Valve numbers given in parenthesis are for example only and refer to polisher No. 1. Corresponding valves on other polishers are series numbered, i.e., M16 for polisher No. 1, M26 for polisher No. 2, M36 for polisher No. 3, etc.

- \_\_\_\_ 4.2.1.1 Before starting to place a polisher in service, contact the Control Room to insure that there is adequate suction pressure to the Condensate Booster Pumps to permit rinsing of the polisher.
- OPEN the standby polisher influent valve (M11) wait 3 minutes until both valves open, then open vent valve M-13 until water flows from vent. OPEN recycle valve (M16) and recycle header valve MC-1 to polisher sump for 5 minutes. Caution should be taken so as not to exceed 2500 gpm on that polishers flow indicator.
- \_\_\_\_ 4.2.1.2 OPEN effluent valve and close recycle valve to the polisher sump when the polisher to be put in service is rinsed in for 5 min. Shut MC-1.
- \_\_\_\_ 4.2.1.3 Remove the exhaust polisher from service by slowly closing its EFFLUENT valve while slowly opening the standby polisher EFFLUENT valve. Make applicable entries in the polisher Record Book.
- NOTE: Flow change not to exceed rate of 25 gpm/sec.
- \_\_\_\_ 4.2.1.4 After the polisher is placed in service place the local air switch for the appropriate polisher inlet valve (M11), inlet bypass (M11BY), and outlet valve (M12) to the OPEN position. Place the local air switch for the polisher removed from service for the inlet valve (M11) inlet bypass (M11BY), and outlet valve (M12) back to the AUTO position.



CCJ  
APR 23 1979

2106-2.2  
Revision 9  
03/21/79

- \_\_\_\_ 4.2.1.5 Adjust effluent valve of polisher being placed on line to match flow of the in-service polisher tanks.

CAUTION should be taken not to lose resin thru vent line, because the polisher vents are not screened.

#### 4.3 Shutdown

- \_\_\_\_ 4.3.1 The Condensate Polishing System will be shut down when the Condensate System is shut down. CLOSE influent and effluent valves for all polisher tanks. Ensure polishers stay full so that resins do not dry out. Make necessary entries in Polisher Record Book.

#### 4.4 Loading Aqueous Ammonia.

- \_\_\_\_ 4.4.1 Insure drum of water is available to vent tank into; the eyewash and shower stations in coagulator building are operational; and a washdown hose is hooked up to domestic water and is available for use.
- \_\_\_\_ 4.4.2 CLOSE WT-V321A, WT-V148, WT-V149 and N<sub>2</sub> bottle isolation.
- \_\_\_\_ 4.4.3 Remove pipe cap from 2" vent hose and immerse in drum of water, then slowly open WT-V149 to vent tank into drum.
- \_\_\_\_ 4.4.4 Open WT-V72; check closed WT-V69. Remove blind flange and hook up truck transfer hose flange.
- \_\_\_\_ 4.4.5 Close WT-V72, Record tank level, then open WT-V69 and commence transfer.
- \_\_\_\_ 4.4.6 When transfer is complete, close WT-V69 and open WT-V72. Drain and remove transfer hose and rebolt blind flange in place.

OCI  
APR 23 1979

2106-2.2  
Revision 9  
03/21/79

- \_\_\_\_ 4.4.7 Record new tank level and close WT-V149.
- \_\_\_\_ 4.4.8 Open WT-V148 and N<sub>2</sub> isolation, to pressurize tank to = 4-5 psi.
- \_\_\_\_ 4.4.9 Replace pipe cap on vent hose and wash down any spillage.

APR 23 1979

2106-2.2  
Revision 9  
03/21/79

10

APPENDIX A  
Valve Line-Up

System:	Condensate Polishing	Date	
Valve No.	Description	Position	Initial
	Condensate Polishing Tanks		
	Manual Valves		
WT-V324A	Recycle to Condenser Iso.	CL	_____
WT-V334B	Polisher (CO-K-1H) Effluent Iso.	OP	_____
M17A	Polisher (CO-K-1H) Effluent Dwnstr.Res.Trap Px	CL	_____
M17B	Polisher (CO-K-1H) Fluffing Air	CL	_____
WT-V414E	Polisher (CO-K-1H) Effluent Grab Sample	CL	_____
WT-V414F	Polisher (CO-K-1H) Effluent Press. Gauge Iso.	OP	_____
WT-V414G	Polisher (CO-K-1H) Effluent Stream Sample Iso.	OP	_____
WT-V414H	Polisher (CO-K-1H) Effluent Stream Sample Rate	*	_____
WT-V414I	Polisher (CO-K-1H) Influent Grab Sample	CL	_____
WT-V414J	Polisher (CO-K-1H) Influent Iso.	OP	_____
WT-V325A	Influent Header Stream Sample Rate	*	_____
WT-V325B	Influent Header Stream Sample Iso.	OP	_____
WT-V325C	Influent Grab Sample	CL	_____
WT-V325D	Influent Line Drain	CL	_____
WT-V325E	Influent Line Vent	CL	_____
WT-FV-10	Polisher CO-K-H Resin Trap Drain	CL	_____
WT-V326B	Polisher (CO-K-1G) Effluent Iso.	OP	_____
M27A	Polisher (CO-K-1G) Effluent Dwnstr.Res.Trap Px	CL	_____
M27B	Polisher (CO-K-1G) Fluffing Air	CL	_____
WT-V424E	Polisher (CO-K-1G) Effluent Grab Sample	CL	_____
WT-V424F	Polisher (CO-K-1G) Effluent Press. Gauge Iso.	OP	_____
WT-V424G	Polisher (CO-K-1G) Effluent Stream Sample Iso.	OP	_____
WT-V424H	Polisher (CO-K-1G) Effluent Stream Sample Rate	*	_____
WT-V424I	Polisher (CO-K-1G) Influent Grab Sample	CL	_____
WT-V424J	Polisher (CO-K-1G) Influent Iso.	OP	_____

\* Rate Set

194 227



APR 23 1979

2106-2.2  
Revision 9  
03/21/79

APPENDIX A  
Valve Line-Up

System:	Condensate Polishing	Date
Valve No.	Description	Position
	Condensate Polishing Tanks	
	Manual Valves	Initial
WT-FV-11	Polisher (CO-K-G) Resin Trap Drain	CL
WT-V327B	Polisher (CO-K-1F) Effluent Iso.	OP
M37A	Polisher (CO-K-1F) Effluent Dwnstrm.Res.Trap Px	CL
M37B	Polisher (CO-K-1F) Fluffing Air	CL
WT-V434E	Polisher (CO-K-1F) Effluent Grab Sample	CL
WT-V434F	Polisher (CO-K-1F) Effluent Press. Gauge Iso.	OP
WT-V434G	Polisher (CO-K-1F) Effluent Stream Sample Iso.	OP
WT-V434H	Polisher (CO-K-1F) Effluent Stream Sample Rate	*
WT-V434I	Polisher (CO-K-1F) Influent Grab Sample	CL
WT-V434J	Polisher (CO-K-1F) Influent Iso.	OP
WT-FV-12	Polisher (CO-K-1F) Resin Trap Drain	CL
WT-V329B	Polisher (CO-K-1E) Effluent Iso.	OP
M47A	Polisher (CO-K-1E) Effluent Dwnstrm.Res.Trap Px	CL
M47B	Polisher (CO-K-1E) Fluffing Air	CL
WT-V444E	Polisher (CO-K-1E) Effluent Grab Sample	CL
WT-V444F	Polisher (CO-K-1E) Effluent Press. Gauge Iso.	OP
WT-V444G	Polisher (CO-K-1E) Effluent Stream Sample Iso.	OP
WT-V444H	Polisher (CO-K-1E) Effluent Stream Sample Rate	*
WT-V444I	Polisher (CO-K-1E) Influent Grab Sample	CL
WT-V444J	Polisher (CO-K-1E) Influent Iso.	OP
WT-FV-13	Polisher (CO-K-1E) Resin Trap Drain	CL
WT-V329A	Influent "DPT" Iso.	OP
WT-V329B	Effluent "DPT" Iso.	OP
WT-V329C	Effluent Line Vent	CL
WT-V329D	Effluent Line Grab Sample	CL
WT-V329E	Effluent Line Drain	CL

194 228

\* Rate Set

10.0

CCJ  
APR 23 1979

2106-2.2  
Revision 9  
03/21/79

APPENDIX A  
Valve Line-Up

System:	Condensate Polishing	Date
Valve No.	Description Condensate Polishing Tanks Manual Valves	Position Initial
WT-V329F	Effluent Header Stream Sample Iso.	OP
WT-V329G	Effluent Header Stream Sample Rate	*
WT-V330A	Resin Inlet Line Iso. to Polishers CO-K-1A to 1D	CL
WT-V330B	Resin Inlet Line Iso. to Polishers CO-K-1E to 1H	CL
WT-V331A	Air Inlet Line Iso. to Polishers CO-K-1E to 1H	CL
WT-V331B	Air Inlet Line Iso. to Polishers CO-K-1A to 1D	CL
WT-V332A	Resin Outlet Line Iso. from Polishers CO-K-1A to 1D	CL
WT-V332B	Resin Outlet Line Iso. from Polishers CO-K-1E to 1H	CL
WT-V333A	Sluice Water Inlet Iso. to Polishers CO-K-1A to 1D	OP
WT-V333B	Sluice Water Inlet Iso. to Polishers CO-K-1E to 1H	OP
WT-V334A	Polisher (CO-K-1D) Effluent Iso.	OP
M57A	Polisher (CO-K-1D) Effluent Dwnstr.Res.Trap Px	CL
M57B	Polisher (CO-K-1D) Fluffing Air	CL
WT-V454D	Polisher (CO-K-1D) Effluent Grab Sample	CL
WT-V454E	Polisher (CO-K-1D) Effluent Press. Gauge Iso.	OP
WT-V454G	Polisher (CO-K-1D) Effluent Stream Sample Iso.	OP
WT-V454F	Polisher (CO-K-1D) Effluent Stream Sample Rate	*
WT-V454I	Polisher (CO-K-1D) Influent Grab Sample	CL
WT-V454J	Polisher (CO-K-1D) Influent Iso.	OP
WT-FV-14	Polisher (CO-K-1D) Resin Trap Drain	CL
WT-FV-15	Polisher (CO-K-1C) Resin Trap Drain	CL
WT-V335B	Polisher (CO-K-1C) Effluent Iso.	OP
WT-M67A	Polisher (CO-K-1C) Effluent Dwnstr.Res.Trap Px	CL
WT-M67B	Polisher (CO-K-1C) Fluffing Air	CL
WT-V464D	Polisher (CO-K-1C) Effluent Grab Sample	CL

\*Rate Set

11.0

194 229

APPENDIX A  
Valve Line-Up

APR 23 1979

2106-2.2  
Revision  
03/21/79 9

System:	Condensate Polishing	Date	
Valve No.	Condensate Polishing Tanks Manual Valves	Position	Initial
WT-V464E	Polisher (CO-K-1C) Effluent Press. Gauge Iso.	OP	_____
WT-V464G	Polisher (CO-K-1C) Effluent Stream Sample Iso.	OP	_____
WT-V464F	Polisher (CO-K-1C) Effluent Stream Sample Rate	*	_____
WT-V464I	Polisher (CO-K-1C) Influent Grab Sample	CL	_____
WT-V464J	Polisher (CO-K-1C) Influent Iso.	OP	_____
WT-V336B	Polisher (CO-K-1B) Effluent Iso.	OP	_____
M77A	Polisher (CO-K-1B) Effluent Dwnstr.Res.Trap Px	CL	_____
M77B	Polisher (CO-K-1B) Fluffing Air	CL	_____
WT-V474D	Polisher (CO-K-1B) Effluent Grab Sample	CL	_____
WT-V474E	Polisher (CO-K-1B) Effluent Press. Gauge Iso.	OP	_____
WT-V474G	Polisher (CO-K-1B) Effluent Stream Sample Iso.	OP	_____
WT-V474F	Polisher (CO-K-1B) Effluent Stream Sample Rate	*	_____
WT-V474I	Polisher (CO-K-1B) Influent Grab Sample	CL	_____
WT-V474J	Polisher (CO-K-1B) Influent Iso.	OP	_____
WT-FV-16	Polisher (CO-K-1B) Resin Trap Drain	CL	_____
WT-V337B	Polisher (CO-K-1A) Effluent Iso.	OP	_____
M87A	Polisher (CO-K-1A) Effluent Dwnstr.Res.Trap Px	CL	_____
M87B	Polisher (CO-K-1A) Fluffing Air	CL	_____
WT-V484D	Polisher (CO-K-1A) Effluent Grab Sample	CL	_____
WT-V484E	Polisher (CO-K-1A) Effluent Press. Gauge Iso.	OP	_____
WT-V484G	Polisher (CO-K-1A) Effluent Stream Sample Iso.	OP	_____
WT-FV-17	Polisher (CO-K-1A) Resin Trap Drain	CL	_____
WT-V484F	Polisher (CO-K-1A) Effluent Stream Sample Rate	*	_____
WT-V484I	Polisher (CO-K-1A) Influent Grab Sample	CL	_____
WT-V484J	Polisher (CO-K-1A) Influent Iso.	OP	_____

\* Rate Set



APR 23 1979

2106-2.2  
Revision 9  
03/21/79

# APPENDIX A

## Valve Line-Up

System:	Condensate Polishing	Date
Valve No.	Description Condensate Polishing Tanks Automatic Valves	Position Initial
M31	Polisher CO-K-1F Influent	A-OP
M32	Polisher CO-K-1F Effluent	A-OP
M33	Polisher CO-K-1F Vent	A-CL
M34	Polisher CO-K-1F Transfer Air In	A-CL
M35	Polisher CO-K-1F Resin In	A-CL
M36	Polisher CO-K-1F Recycle to Condenser	A-CL
M38	Polisher CO-K-1F Sluice Water In	A-CL
M39	Polisher CO-K-1F Resin Out	A-CL
M31 BY	Polisher CO-K-1F Influent Bypass	A-OP
M41	Polisher CO-K-1E Influent	A-OP
M42	Polisher CO-K-1E Effluent	A-OP
M43	Polisher CO-K-1E Vent	A-CL
M44	Polisher CO-K-1E Transfer Air In	A-CL
M45	Polisher CO-K-1E Resin In	A-CL
M46	Polisher CO-K-1E Recycle to Condenser	A-CL
M48	Polisher CO-K-1E Sluice Water In	A-CL
M49	Polisher CO-K-1E Resin Out	A-CL
M41 BY	Polisher CO-K-1E Influent Bypass	A-OP
M51	Polisher CO-K-1D Influent	A-OP
M52	Polisher CO-K-1D Effluent	A-OP
M53	Polisher CO-K-1D Vent	A-CL
M54	Polisher CO-K-1D Transfer Air In	A-CL
M55	Polisher CO-K-1D Resin In	A-CL

APR 23 1979

2106-2.2  
Revision 9  
03/21/79APPENDIX A

## Valve Line-Up

System:	Condensate Polishing	Date
Valve No.	Description	Position
	Condensate Polishing Tanks Automatic Valves	Initial
M56	Polisher CO-K-1D Recycle to Condenser	A-CL
M58	Polisher CO-K-1D Sluice Water In	A-CL
M59	Polisher CO-K-1D Resin Out	A-CL
M51 BY	Polisher CO-K-1D Influent Bypass	A-OP
MC1	Drain to Cond. Polishers Regeneration Sump	A-CL
MC2	Header Recycle to Condenser	A-CL
M11	Polisher CO-K-1H Influent	A-OP
M12	Polisher CO-K-1H Effluent	A-OP
M13	Polisher CO-K-1H Vent	A-CL
M14	Polisher CO-K-1H Transfer Air Inlet	A-CL
M15	Polisher CO-K-1H Resin Inlet	A-CL
M16	Polisher CO-K-1H Recycle to Condenser	A-CL
M18	Polisher CO-K-1H Sluice Water Inlet	A-CL
M19	Polisher CO-K-1H Resin Outlet	A-CL
M11 BY	Polisher CO-K-1H Influent Bypass	A-OP
M21	Polisher CO-K-1G Influent	A-OP
M22	Polisher CO-K-1G Effluent	A-OP
M23	Polisher CO-K-1G Vent	A-CL
M24	Polisher CO-K-1G Transfer Air Inlet	A-CL
M25	Polisher CO-K-1G Resin Inlet	A-CL
M26	Polisher CO-K-1G Recycle to Condenser	A-CL
M28	Polisher CO-K-1G Sluice Water Inlet	A-CL
M29	Polisher CO-K-1G Resin Outlet	A-CL

APPENDIX A

Valve Line-Up

System:	Condensate Polishing	Date	
Valve No.	Description	Position	Initial
	Condensate Polishing Tanks		
	Automatic Valves		
M21 BY	Polisher CO-K-1G Influent Bypass	A-OP	_____
M61	Polisher CO-K-1C Influent	A-OP	_____
M62	Polisher CO-K-1C Effluent	A-OP	_____
M63	Polisher CO-K-1C Vent	A-CL	_____
M64	Polisher CO-K-1C Transfer Air In	A-CL	_____
M65	Polisher CO-K-1C Resin In	A-CL	_____
M66	Polisher CO-K-1C Recycle to Condenser	A-CL	_____
M68	Polisher CO-K-1C Sluice Water In	A-CL	_____
M69	Polisher CO-K-1C Resin Out	A-CL	_____
M61 BY	Polisher CO-K-1C Influent Bypass	A-OP	_____
M71	Polisher CO-K-1B Influent	A-OP	_____
M72	Polisher CO-K-1B Effluent	A-OP	_____
M73	Polisher CO-K-1B Vent	A-CL	_____
M74	Polisher CO-K-1B Transfer Air In	A-CL	_____
M75	Polisher CO-K-1B Resin In	A-CL	_____
M76	Polisher CO-K-1B Recycle to Condenser	A-CL	_____
M78	Polisher CO-K-1B Sluice Water In	A-CL	_____
M79	Polisher CO-K-1B Resin Out	A-CL	_____
M71 BY	Polisher CO-K-1B Influent Bypass	A-OP	_____
M81	Polisher CO-K-1A Influent	A-OP	_____
M82	Polisher CO-K-1A Effluent	A-OP	_____
M83	Polisher CO-K-1A Vent	A-CL	_____
M84	Polisher CO-K-1A Transfer Air In	A-CL	_____



2106-2.2  
Revision 9  
03/21/79  
APR 23 1979

APPENDIX A

Valve Line-Up

System:	Condensate Polishing	Date
Valve No.	Description Condensate Polishing Tanks Automatic Valves	Position Initial
M85	Polisher CO-K-1A Resin In	A-CL
M86	Polisher CO-K-1A Recycle to Condenser	A-CL
M88	Polisher CO-K-1A Sluice Water In	A-CL
M89	Polisher CO-K-1A Resin Out	A-CL
M81 BY	Polisher CO-K-1A Influent Bypass	A-OP

APR 23 1979

2106-2.2  
Revision 9  
03/21/79

APPENDIX A  
Valve Line-Up

System:	Condensate Polishing	External Regeneration	Date	
Valve No.	Description	Station Manual Valves	Position	Initial
WT-V316A	Caustic Storage Tank Drain		CL	_____
WT-V317A	Hot Water Tank Outlet Iso.		OP	_____
WT-V317B	Hot Water Tank Drain		CL	_____
WT-V317C	Hot Water Tank Inlet Iso.		CL	_____
WT-V318A	Caustic Dilution Water Line Iso.		OP	_____
WT-V318B	Acid Dilution Water Line Iso.		OP	_____
WT-V319A	Mixing & Storage Tank Drain		CL	_____
WT-V319B	Mixing & Storage Tank Conductivity Cell Rate		*	_____
WT-V319C	Mixing & Storage Tank Grab Sample		CL	_____
WT-V320A	Regeneration Tank Air to Vibrator Rate		*	_____
WT-V320B	Regeneration Tank Dilute Acid In	Locked	CL	_____
WT-V320C	Regeneration Tank Grab Sample		CL	_____
WT-V320D	Regeneration Tank Conductivity Cell Rate		*	_____
WT-V320E	Regeneration Tank Drain		CL	_____
WT-V320F	Regeneration Tank Conductivity Cell Rate		*	_____
WT-V320G	Regeneration Tank Chemical Injection Line Drain		CL	_____
WT-FV-84	Resin Addition to Receiving Tank		CL	_____
WT-V320H	Sluice Water to Polishers Rate		*	_____
WT-V320I	Sluice Water to Polishers Iso.		OP	_____
WT-V320J	Sluice Water to Regeneration Station Iso.		OP	_____
WT-V321A	Aqueous Ammonia Storage Tank Drain		CL	_____
WT-V321B	Aqueous Ammonia Pump AM-P-4C Discharge Px		CL	_____
WT-V321C	Aqueous Ammonia Pump AM-P-4B Discharge Px		CL	_____
WT-V321D	Aqueous Ammonia Pump AM-P-4A Discharge Px		CL	_____

\* Rate Set

APR 23 1979

2106-2.2  
Revision 9  
03/21/79

APPENDIX A  
Valve Line-Up

System:	Condensate Polishing	External Regeneration	Date	
Valve No.	Description	Station Manual Valves	Position	Initial
WT-V321E	Aqueous Ammonia Pump AM-P-4B Discharge Iso.		OP	_____
WT-V321F	Aqueous Ammonia Pump AM-P-4B Surge Chamber Drain		CL	_____
WT-V321G	Aqueous Ammonia Pump AM-P-4A Discharge Iso.		OP	_____
WT-V321H	Aqueous Ammonia Pump AM-P-4A Surge Chamber Drain		CL	_____
WT-V321I	Aqueous Ammonia Pump AM-P-4C Discharge Iso.		OP	_____
WT-V321J	Aqueous Ammonia Pump AM-P-4C Surge Chamber Drain		CL	_____
WT-V321L	Demin. Water to Sulphite Feed Hdr.		CL	_____
WT-V321M	Sodium Sulphite Discharge Header Rate		*	_____
WT-V322A	Mixing & Motive Air to Pol. and Regen. St. Iso.		OP	_____
WT-V322B	Mixing Air to Reg. Station Iso.		OP	_____
WT-V322C	Sodium Sulphite Pump (WT-P-15A) Disch. Iso.		CL	_____
WT-V322D	Sodium Sulphite PUmp (WT-P-15B) Disch. Iso.		CL	_____
WT-V323A	Dilution Water to Sodium Sulphite Header Rate		*	_____
WT-V323B	Dilution Water to Aqueous Ammonium Header Rate		*	_____
WT-V323C	Sodium Sulphite Pump WT-P-15A Inlet Iso.		CL	_____
WT-V323D	Sodium Sulphite Pump WT-P-15B Inlet Iso.		CL	_____
WT-V323E	Sodium Sulphite Tank WT-H-1 Drain		CL	_____
WT-V323F	Sodium Sulphite Tank Demin. Water Rate		*	_____
WT-V323G	Dilute Caustic Line Grab Sample		CL	_____
WT-V323H	Dilute Acid Line Grab Sample		CL	_____
WT-FV-18	Dilute Caustic Conductivity Cell Rate		*	_____

\* Rate Set



APR 23 1979

2106-2.2  
Revision 9  
03/21/79APPENDIX A

## Valve Line-Up

System:	Condensate Polishing	Date	
Valve No.	Description	Position	Initial
	External Regeneration Station		
	Automatic Valves		
S9	Mix & Storage Tank Backwash Water Inlet	A-CL	_____
S10	Mix & Storage Tank Backwash Outlet	A-CL	_____
S11	Mix & Storage Tank Sluice Water Inlet	A-CL	_____
C1	Regeneration Tank Resin In from Polishers	A-CL	_____
C2	Regeneration Tank Aqueous Ammonia Inlet	A-CL	_____
C3	Regeneration Tank Dilute Acid Inlet	A-CL	_____
C4	Regeneration Tank Rinse Waste Outlet	A-CL	_____
C5	Regeneration Tank Backwash Water Inlet	A-CL	_____
C6	Regeneration Tank Mixing Air Inlet	A-CL	_____
C7	Regeneration Tank Sluice Water Inlet	A-CL	_____
C8	Regeneration Tank Resin Transfer to Mix. & Storage Tank	A-CL	_____
C9	Regeneration Tank Dilute Caustic Inlet	A-CL	_____
C10	Regeneration Tank Sodium Sulphite Inlet	A-CL	_____
C11	Regeneration Tank Motive Air Inlet	A-CL	_____
C12	Regeneration Tank Vent	A-CL	_____
C13	Regeneration Tank Backflush Wastes Outlet	A-CL	_____
C14	Regeneration Tank Rinse Water	A-CL	_____
C15	Regeneration Tank Resin from Mix & Stg. Tk.	A-CL	_____
C16	Regeneration Tank Flush Water Inlet	A-CL	_____
C17	Regeneration Tank Aqueous Ammonia Inlet	A-CL	_____
R1P	Concentrated Acid Pump Discharge	A-CL	_____
R2P	Concentrated Acid Discharge to Dilute Acid "Tee"	A-CL	_____

APPENDIX A

Valve Line-Up

APR 23 1979

2106-2.2  
Revision 9  
03/21/79

System:	Condensate Polishing	Date	
Valve No.	Description	Position	Initial
	External Regeneration Station Automatic Valves		
R3P	Concentrated Acid Discharge to "N" Tank	A-CL	
R4P	Dilution Water Discharge to Acid Mix "Tee"	A-CL	
R5P	Concentrated Caustic Pump Discharge	A-CL	
R6P	Concentrated Caustic Discharge to Dilute Caustic "Tee"	A-CL	
R7P	Concentrated Caustic Discharge to "N" Tank	A-CL	
R8P	Dilution Water Discharge to Caustic Mix "Tee"	A-CL	
R9P	Sodium Sulphite Pump Discharge to Mix "Tee"	A-CL	
R10P	Dilution Water Discharge to Sodium Sulphite Mix "Tee"	A-CL	
R11P	Aqueous Ammonia Pump Discharge to Mix "Tee"	A-CL	
R12P	Dilution Water Discharge to Aqueous Ammonia Mix "Tee"	A-CL	
X1	Sluicing Wastes to Drain Pot	A-CL	
X2	Regeneration Wastes to "N" Tank	A-OP	
PR-1	Mix & Motive Air Regulator	*	
PR-2	Mix Air Regulator	*	
SV-1	Caustic Dilution Water Blend	A	
S1	Mix & Storage Tk. Motive Air Inlet	A-CL	
S2	Mix & Storage Tk. Vent	A-CL	
S4	Backflush Waste to "N" Tk.	A-CL	
S5	Mix & Storage Tk. Rinse Water Inlet	A-CL	
S6	Mix & Storage Tk. Flush Wastes	A-CL	
S7	Mix & Storage Tk. Mixing Air Inlet	A-CL	
S8	Mix & Storage Tk. Resin Transfer to Polishers	A-CL	

\* Rate Set

20.0

194 238

APR 23 1979

2106-2.2  
Revision 9  
03/21/79

# APPENDIX A

## Valve Line-Up

System:	Condensate Polishing	Date
Valve No.	Description	Position
WT-V103	Sump Disch. Hdr. Radiation Monitor Outlet Iso.	OP
WT-V104	Sump Disch. Hdr. Radiation Monitor Inlet Iso.	OP
WT-V105A	Sump Pump WT-P-19A Discharge Iso.	OP
WT-V105B	Sump Pump WT-P-19B Discharge Iso.	OP
WT-V115	Regeneration Sump Effluent Control to Blowdown	A-OP
WT-V118	Regeneration Station Effluent Control to "N" Tank	A-OP
WT-V119	Regeneration Station Effluent Control to Misc. Waste Hold-Up Tank	A-CL
WT-V121	Regeneration Sump Effluent Control to Misc. Waste Hold-Up Tank	A-CL
WT-V123A	Cond. Polishing Regeneration Wastes to Misc. Waste Hold-Up Tank Iso.	OP
WT-V123B	Cond. Polishing Regeneration Sump Disch. to Misc. Waste Hold-Up Tank Iso.	OP
WT-V131	Line Vent Con. Polisher to Misc. Waste Tank	CL
WT-V132	Line Vent Iso. Cond. Polisher to Misc. Waste Tank	CL



APR 23 1979

2106-2.2  
Revision 9  
03/21/79

# APPENDIX A

## Valve Line-Up

System:	Condensate Polishing	Date		
Valve No.	Description	Ammonia & Hydrazine Feed	Position	Initial
		Manual Valves		
WT-V338A	Ammonium Hydroxide Pump (AM-P-2) Inlet Iso.		OP	_____
WT-V338B	Ammonium Hydroxide Tank (AM-T-1) Drain		CL	_____
WT-V338C	Ammonium Hydroxide Tank Condensate Fill		CL	_____
WT-V338D	Ammonium Hydroxide Measuring Tank (AM-T-4) Drain		CL	_____
WT-V338E	Ammonium Hydroxide Pump (AM-P-2) Discharge Iso.		OP	_____
WT-V339A	Hydrazine Pump (AM-P-1B) Inlet Iso.		OP	_____
WT-V339B	Hydrazine Pump (AM-P-1A) Inlet Iso.		OP	_____
WT-V339C	Hydrazine Tank (AM-T-2) Drain		CL	_____
WT-V339D	Hydrazine Tank Condensate Fill		CL	_____
WT-V339E	Hydrazine Measuring Tank (AM-T-5) Drain		CL	_____
WT-V339F	Hydrazine Pump (AM-P-1B) Discharge Iso.		OP	_____
WT-V339G	Hydrazine Pump (AM-P-1A) Discharge Iso.		OP	_____
WT-V93	Ammonium Hydroxide Injection Iso.		OP	_____
WT-V94	Hydrazine Injection Iso.		OP	_____

*CS*

2106-2.2  
Revision 9  
03/21/79

APR 23 1979

APPENDIX A  
Valve Line-Up

System:	Condensate Polishing	Date	
Valve No.	Description	Position	Initial
WT-IV-47	WT-PT-7395 Iso.	OP	_____
WT-IV-48	WT-PT-7395 Iso.	OP	_____
WT-IV-49	WT-PT-7395 Equilizing Vlv.	CL	_____
WT-IV-50	WT-FT-7394 Iso.	OP	_____
WT-IV-51	WT-FT-7394 Iso.	OP	_____
WT-IV-52	WT-FT-7394 Equilizing Vlv.	CL	_____
WT-IV-53	WT-DPT-7394 Iso.	OP	_____
WT-IV-54	WT-DPT-7394 Iso.	OP	_____
WT-IV-55	WT-DPT-7394 Equilizing Vlv.	CL	_____
WT-IV-7	WT-FT-7393 Iso.	OP	_____
WT-IV-8	WT-FT-7393 Iso.	OP	_____
WT-IV-9	WT-FT-7393 Equilizing Vlv.	CL	_____
WT-IV-10	WT-PI-2044 Gauge Iso.	OP	_____
WT-IV-11	Test Connection	CL	_____
WT-IV-12	WT-FT-7392 Iso.	OP	_____
WT-IV-13	WT-FT-7392 Iso.	OP	_____
WT-IV-14	WT-FT-7392 Equilizing Vlv.	CL	_____
WT-IV-15	WT-PI-2043 Gauge Iso.	OP	_____
WT-IV-16	Test Connection	CL	_____
WT-IV-17	WT-FT-7391 Iso.	OP	_____
WT-IV-18	WT-FT-7391 Iso.	OP	_____
WT-IV-19	WT-FT-7391 Equilizing Vlv.	CL	_____

APPENDIX A  
Valve Line-Up

System:	Condensate Polishing	Date	
Valve No.	Description	Position	Initial
WT-IV-20	WT-PI-2042 Gauge Iso.	OP	_____
WT-IV-21	Test Connection	CL	_____
WT-IV-22	WT-FT-7390 Iso.	OP	_____
WT-IV-23	WT-FT-7390 Iso.	OP	_____
WT-IV-24	WT-FT-7390 Equilizing Vlv.	CL	_____
WT-IV-25	WT-PI-2041 Gauge Iso.	OP	_____
WT-FV-19	Polisher CO-K-1H DPSI 7386 Isolation	OP	_____
WT-FV-20	Polisher CO-K-1H DPSI 7386 Isolation	OP	_____
WT-FV-21	Polisher CO-K-1G DPSI 7387 Isolation	OP	_____
WT-FV-22	Polisher CO-K-1G DPSI 7387 Isolation	OP	_____
WT-FV-23	Polisher CO-K-1F DPSI 7388 Isolation	OP	_____
WT-FV-24	Polisher CO-K-1F DPSI 7388 Isolation	OP	_____
WT-FV-25	Polisher CO-K-1E DPSI 7389 Isolation	OP	_____
WT-FV-26	Polisher CO-K-1E DPSI 7389 Isolation	OP	_____
WT-FV-27	Polisher CO-K-1D DPSI 7390 Isolation	OP	_____
WT-FV-28	Polisher CO-K-1D DPSI 7390 Isolation	OP	_____
WT-FV-29	Polisher CO-K-1C DPSI 7391 Isolation	OP	_____
WT-FV-30	Polisher CO-K-1C DPSI 7391 Isolation	OP	_____
WT-FV-31	Polisher CO-K-1B DPSI 7392 Isolation	OP	_____
WT-FV-32	Polisher CO-K-1B DPSI 7392 Isolation	OP	_____
WT-FV-33	Polisher CO-K-1A DPSI 7393 Isolation	OP	_____
WT-FV-34	Polisher CO-K-1A DPSI 7393 Isolation	OP	_____



APR 23 1979

2106-2.2  
Revision 9  
03/21/79

APPENDIX A  
Valve Line-Up

System:	Condensate Polishing	Date	
Valve No.	Description	Position	Initial
WT-FV-35	WT-FT-7396 Iso.	OP	_____
WT-FV-36	WT-FT-7396 Iso.	OP	_____
WT-FV-37	WT-FT-7396 Equilizing Vlv.	CL	_____
WT-FV-56	CO-K-1G Resin Sample Iso.	T	_____
WT-FV-57	CO-K-1G Test Conn.	CL	_____
WT-FV-58	CO-K-1G Test Conn	CL	_____
WT-FV-59	CO-K-1H Resin Sample Iso.	T	_____
WT-FV-60	CO-K-1H Test Conn	CL	_____
WT-FV-61	CO-K-1H Test Conn	CL	_____
WT-FV-62	Influent Resin Sample Iso.	T	_____
WT-FV-63	Influent Test Conn	CL	_____
WT-FV-64	Influent Test Conn	CL	_____
WT-FV-65	Effluent Resin Sample Iso.	T	_____
WT-FV-66	Effluent Test Conn	CL	_____
WT-FV-67	Effluent Test Conn	CL	_____
WT-V-137A	CO-K-1A Sample Drain Vlv	OP	_____
WT-V-137B	CO-K-1B Sample Drain Vlv	OP	_____
WT-V-137C	CO-K-1C Sample Drain Vlv	OP	_____
WT-V-137D	CO-K-1D Sample Drain Vlv	OP	_____
WT-V-137E	CO-K-1E Sample Drain Vlv	OP	_____
WT-V-137F	CO-K-1F Sample Drain Vlv	OP	_____
WT-V-137G	CO-K-1G Sample Drain Vlv	OP	_____

APPENDIX A  
 Valve Line-Up

System:	Condensate Polishing	Date	
Valve No.	Description	Position	Initial
WT-V-137H	CO-K-1H Sample Drain Vlv	OP	_____
WT-V-137J	Influent Sample Drain Vlv	OP	_____
WT-V-137K	Effluent Sample Drain Vlv	OP	_____
WT-FV-38	CO-K-1A Resin Sample Iso.	T	_____
WT-FV-39	CO-K-1A Test Conn	CL	_____
WT-FV-40	CO-K-1A Test Conn	CL	_____
WT-FV-41	CO-K-1B Resin Sample Iso.	T	_____
WT-FV-42	CO-K-1B Test Conn	CL	_____
WT-FV-43	CO-K-1B Test Conn	CL	_____
WT-FV-44	CO-K-1C Resin Sample Iso.	T	_____
WT-FV-45	CO-K-1C Test Conn	CL	_____
WT-FV-46	CO-K-1C Test Conn	CL	_____
WT-FV-47	CO-K-1D Resin Sample Iso.	T	_____
WT-FV-48	CO-K-1D Test Conn	CL	_____
WT-FV-49	CO-K-1D Test Conn	CL	_____
WT-FV-50	CO-K-1E Resin Sample Iso.	T	_____
WT-FV-51	CO-K-1E Test Conn	CL	_____
WT-FV-52	CO-K-1E Test Conn	CL	_____
WT-FV-53	CO-K-1F Resin Sample Iso.	T	_____
WT-FV-54	CO-K-1F Test Conn	CL	_____
WT-FV-55	CO-K-1F Test Conn	CL	_____

2106-2.2  
Revision 9  
03/21/79

Signatures of those performing/supervising valve line-up

[illegible]



APR 23 1979

2106-2.2  
Revision 9  
03/21/79

THREE MILE ISLAND NUCLEAR STATION  
UNIT #2 OPERATING PROCEDURE 2106-2.2  
CONDENSATE POLISHING SYSTEM  
Regeneration Section  
2106-2.2B

1.0 REFERENCES

1.1 Drawings Applicable for Operation.

- 1.1.1 Make-Up Water Treatment and Condensate Polishing, B&R Dwg. 2006.
- 1.1.2 Condensate Demineralizer Mixed Bed Polisher System, L\*A Water Conditioning Co. Dwg. 015-00-0405.
- 1.1.3 Condensate Demineralizer External Regeneration System, L\*A Water Conditioning Co. Dwg. 015-00-0406.

1.2 Operating Procedures Applicable for Operation.

- 1.2.1 2104-2.1 Cycle Make-Up Pretreatment.
- 1.2.2 2104-2.2 Demineralized Service Water.
- 1.2.3 2104-2.3 Instrument Air.
- 1.2.4 2104-2.9 Demineralizing System.
- 1.2.5 2104-2.10 Service Air.
- 1.2.6 2106-2.1 Condensate.
- 1.2.7 2106-2.4 Feedwater.
- 1.2.8 2107-1.1 BOP Electrical.

1.3 Manufacturers Instruction Manual.

- 1.3.1 L\*A Water Purification System, Volumes I thru V B&R File # (15.00).

1.4 Applicable System Descriptions.

- 1.4.1 Feedwater and Condensate, Index No. 4A.

- 1.4.2     Condensate Polishing, Index No. 4B.
- 1.4.3     Make-Up Water Treatment, Index No. 4C.
- 1.5     Curves, Tables, etc.
- 1.5.1     Table No. 2B Remote Regeneration Station - Automatic/Manual  
           Valve Sequence, Page 6.0.
- 2.0     LIMITS AND PRECAUTIONS
- 2.1     Equipment.
- 2.1.1     Visually inspect through the sight glasses the applicable  
           polisher tank or external regeneration tank before and after  
           each resin transfer.
- 2.2     Administrative.
- 2.2.1     The Condensate Polishing System demineralizes feedwater which  
           potentially contains radioactive material should a Primary to  
           Secondary Leak Exist. Since this radioactive material would  
           be concentrated in the mixed bed resin, the resin must be  
           treated as potentially radioactive under this condition.
- 2.2.2     Ensure the heat tracing on the system components and piping is  
           energized for both freeze protection and to prevent chemical  
           crystallization.  
           CAUTION: The heat tracing temperature for 50% caustic lines  
                     is 75°F to prevent crystallization and caustic  
                     stress cracking of piping.
- 2.2.3     Adequate safety precautions for strong chemical solutions must  
           be observed when working with caustic or acid.
- 2.2.4     While polishers are in service the local air switches for the  
           inlet valves, inlet bypass valves and outlet valves should be

placed in the OPEN position. When a polisher is removed from service or is in standby, the local air switches for these valves should be in AUTO.

- 2.2.5 Each step of the regeneration procedure should be initialed as performed. Each operator who works on a regeneration step and initials it should initial and sign Data Sheet 51 in the place provided. After completed regeneration cycle the initialed procedure and data sheet for the appropriate bed should be forwarded to the Operations Engineer.

### 3.0 PREREQUISITES

Initial Each Step.

- \_\_\_ 3.1 Electrical power available per 2107-1.1.

<u>Component</u>	<u>Source</u>	<u>Unit</u>
WF-P-13	2-31D	3D
WT-P-14	2-31D	3E
AM-P-4A/B/C	2-31D	4B/4C/4D
WT-P-15A/B	2-31D	3F/4A
WT-P-19A	2-31A	10A
WT-P-19B	2-41A	7B

- \_\_\_ 3.2 Instrument Air in operation per 2104-2.3.

- \_\_\_ 3.3 Service Air in operation per 2104-2.10.

- \_\_\_ 3.4 Demineralized Water in operation per 2104-2.2.

- \_\_\_ 3.5 Condensate polisher regeneration sump pumps (WT-P-19A/B) in AUTO.

- \_\_\_ 3.6 Neutralization tank (WT-T-9) and neutralized effluent disposal pumps (WT-P-8A/B) in operation per 2104-2.9.



ccf  
APR 23 1979

2106-2.2  
Revision 9  
J3/21/79

- \_\_\_\_ 3.7 Check the level in the neutralizing tank. <7000 gallons
- \_\_\_\_ 3.8 Acid storage tank (WT-T-7), caustic storage tank (WT-T-8), and aqueous ammonia storage tank (AM-T-6), filled to minimum level.
- \_\_\_\_ 3.9 Valve line-up complete per 2106-2.2A, Appendix A.
- \_\_\_\_ 3.10 Demineralizer Water available from Unit #1.

4.0 PROCEDURE

Initial Each Step.

2106-2.2  
Revision 9  
03/21/79  
APR 22 1979

2106-2.2  
Revision 9  
03/21/79

#### 4.1 Regeneration

4.1.1 At Panel 304 place extension controls in the following position.

S1	AUTO	C8	AUTO
S2	AUTO	C9	AUTO
S4	AUTO	C11	AUTO
S6	AUTO	C12	AUTO
S7	AUTO	C13	AUTO
S11	AUTO	C14	AUTO
R1,2,3	AUTO	C15	AUTO
R4	AUTO	C16	AUTO
R5,6,7	AUTO	C17	AUTO
R8	AUTO	S5A	AUTO
R9	AUTO	S5B	AUTO
R10	AUTO	X1-X2	AUTO
R11	AUTO	Hot Water Heater	ON
R12	AUTO	Vibrator	AUTO
C2	AUTO	WT-P-13	OFF
C3	AUTO	WT-P-14	AUTO
C4	AUTO	AM-P-4A	OFF
C5	AUTO	AM-P-4B	OFF
C6	AUTO	AM-P-4C	OFF
C7	AUTO		

APR 23 1979

2106-2.2  
Revision 9  
03/21/79

55

4.1.2 At Panel 304 set the timers as follows:

MODULE

C	Step 10	0 Min	_____
C	Step 11	0 Min	_____
C	Step 12	0 Min	_____
C	Step 13	0 Min	_____
C	Step 14	20 Min	_____
C	Step 15	20 Min	_____
D	Step 16	0 Min	_____
D	Step 16A	0 Min	_____
D	Step 17	0 Min	_____
D	Step 18	0 Min	_____
D	Step 19	65 Min	_____
D	Step 20	60 Min	_____
F	Step 21	15 Min	_____
F	Step 21A	0 Min	_____
F	Step 21B	10 Min	_____
F	Step 22	30 Min	_____
G	Step 23	5 Min	_____
G	Step 24	20 Min	_____
H	Step 25	30 Min	_____
H	Step 26	0 Min	_____
H	Step 27	30 Min	_____
E	Step 28	120 Min	_____
E	Step 29	30 Min	_____



APR 23 1979

2106-2.2  
Revision 9  
03/21/79

#### 4.1.3 Place Logic Module Selector Switches in the following positions:

Mode of Operation	AUTO	_____
Extend Cycle Step Control	TIME	_____
Module C	STOP/ALARM	_____
Module D	STOP/ALARM	_____
Module E	STOP/ALARM	_____
Module F	STOP/ALARM	_____
Module G	STOP/ALARM	_____
Module H	STOP/ALARM	_____

Valve number given for the operation of the polishers are for example only, and refer to polisher #1. Corresponding valves on other polishers are series numbered; i.e., M-16 for polisher #1, M-26 for polisher #2, etc.

When any step timer is used all valves and pumps associated with that step must be in AUTO.

Table 2B is your reference for all valve positions and flow rates associated with a particular automatic step. Any other pertinent information is in the remarks section.

#### 4.1.4 Resin Transfer From Polisher To Receiving Tank

     A. Set up Receiving Tank to receive exhausted resin;

         1. OPEN valves C-1, C-4, and C-12.

         2. Place X1-X2 switch to AUTO.

         3. Put the "A" conductivity recorder to HAND.

         4. Inspect tank to assure it is empty.

     B. Set up Unit 2 Demin Water for Transfer:

         1. OPEN DW-V 453 all the way.

         2. CHECK open DW-V499.

APR 23 1979

2106-2.2  
Revision 9  
03/21/79

- \_\_\_\_ C. Set up fluffing air: OPEN SA-V401.
- \_\_\_\_ D. Set up resin Sluice Line:
- \_\_\_\_ 1. If transferring from Polisher #1 - #4, OPEN WT-V332B, CLOSE WT-V332A.
- \_\_\_\_ 2. If transferring from Polisher #5 - #8, OPEN WT-V322A, CLOSE WT-V332B.
- \_\_\_\_ E. Transfer Exhausted Resin to Receiving Tank As Follows:
- \_\_\_\_ 1. OPEN Polisher Vent M-13, wait until pressure is vented off.
- \_\_\_\_ 2. OPEN Demin Water Inlet M-18, flow should be 60  $\pm$  10 GPM.
- \_\_\_\_ 3. Assure resin is swirling, wait until water is flowing from Polisher Vent. Allow to swirl for approximately 30 minutes. Every 10 minutes give the bed a bump with fluffing air (WT-17B valve).
- \_\_\_\_ 4. OPEN Resin Outlet M-19, and CLOSE Vent M-13.
- \_\_\_\_ 5. Resin will be transferred at first using only Sluice Water. Check Sluice Line Sight Glass and Receiving Tank to verify resin is transferring.
- \_\_\_\_ 6. Continue transfer when top of Resin Bed is visible in lower sight glass. CLOSE Sluice Water M-18 and OPEN Fluffing air WT-V-17B.
- \_\_\_\_ 7. Watch in bottom sight glass as water level goes below bottom laterals - then OPEN Vent M-13 and Sluice Water M-18. CLOSE Resin outlet M-19.

APR 23 1979

2106-2.2  
Revision 9  
03/21/79

8. Allow bubbling water/resin mixture to rise to top of bottom sight glass then CLOSE M-13, M-18 and OPEN M-19.
9. Watch in bottom sight glass as tank drains. There must be no resin mounds above tank laterals. If there are then repeat steps 4.1.4.E 7-9. This time OPEN and CLOSE fluffing air valve while refilling tank to top of bottom sight glass. Repeat at least 3 times or more is needed.
10. When transfer is complete close WT-V17B OPEN M-13 to vent polisher then CLOSE M-13 and M-19.
- F. On Receiving Tank CLOSE C-1 and C-4. OPEN C-14 to 120 GPM position to refill tank. When water comes out Vent CLOSE C-14 and C-12.
- G. CLOSE SA-V401.
- H. CLOSE DW-V453.
- I. Begin to fill out both Regeneration Data Sheets.

4.1.5 Transfer Resin From Storage Tank To Polisher

- A. Vent and drain desired Polisher as follows:
1. Open M-13, M-16 and MC-1. Drain until polisher is dry. (Valves are for #1 Polisher use corresponding Valves for #2 thru #8).
- B. If transferring to Polisher #5 - #8, shut WT-V330A and open WT-V330B.



- \_\_\_\_ C. If transferring to Polishers #1 - #4, shut WT-V330B and open WT-V330A.
- \_\_\_\_ D. Line-up Polisher to receive resin by opening M-13, M-16, M-15 and MC-1.
- \_\_\_\_ E. Line-up Demin Water from Unit #1 by verifying the pump is running and open DW-V172.
- \_\_\_\_ F. Open SA-V238.
- \_\_\_\_ G. Line-up storage tank to transfer resin by opening S-2, S-11.
- \_\_\_\_ H. Verify resin is swirling in bottom sight glass and there is flow (~75 GPM) indicated on local flow indicator. Do this quickly so the resin will not separate.

NOTE: If no Demin Water flow check source Unit #1. If water available, cycle mixing Air Valve S-7 to loosen resin.

- \_\_\_\_ I. To Transfer:
  - \_\_\_\_ 1. OPEN S-8
  - \_\_\_\_ 2. CLOSE S-2 "In This Order"
  - \_\_\_\_ 3. OPEN S-7

Check correct flows per Table 2B.

- \_\_\_\_ J. After Resin Level passes well below Lower Sight Glass on Storage Tank, Close Polisher Drain Valve M-16.
- \_\_\_\_ K. Let transfer continue until water flows from Polisher Vent. Then Close S-7, S-8, and S-11 by placing them to AUTO. Open S-2 to vent the Storage Tank.

APR 23 1979

2106-2.2

APR 23 1979

Revision 9  
03/21/79

- \_\_\_ L. Close M-13, M-15 and MC-1 to isolate the Polisher.
- \_\_\_ M. Close SA-V238 if not continuing with 4.1.6.
- \_\_\_ N. Verify Resin Level in the Regenerated Polisher is in the Upper Sight Glass.
- \_\_\_ O. Enter Regeneration in Polisher Record Log Book.
- \_\_\_ P. The next step is to Regenerate the bed now in the receiving tank. To do this go to Step 4.1.6.

\_\_\_ 4.1.6 Mechanical Cleaning

NOTE: If regeneration is short Regen. see Appendix C.

- \_\_\_ A. Set up Module H Timer as follows:
  - Step 25 - 30 minutes
  - Step 26 - 0 minutes
  - Step 27 - 30 minutes
- \_\_\_ B. Put vibrator to HAND.
- \_\_\_ C. Open SA-V238 and initiate Module H.
  - \_\_\_ 1. While in Step 25, turn C-5 to the 28 GPM position and adjust flow to 28 GPM using the correct air regulator.
  - \_\_\_ 2. Watch Air Flow Gage. If it drops to 100 SCFM the screen must be backwashed as follows: Put C-6 and C-12 to OFF, C-16 and C-4 to HAND for 30 seconds; then place C-16, C-4, C-12, and C-6 to AUTO. Repeat as necessary to maintain air flow.
  - \_\_\_ 3. At the end of Step 25 place C-5 in AUTO and CLOSE SA-V238.

APR 23 1979

2106-2.2  
Revision 9  
03/21/79

4. When the second part of Step 27 starts insure that the flow does not exceed 100 gpm to prevent unnecessary loss of resin.

D. Repeat Steps A, B, C of this procedure 2 or 3 times. If water is still dirty the backwash of Section 4.1.6 will flush out the remainder.

E. Put vibrator to AUTO.

4.1.7 Backwash

A. Set up Module C Timers as follows:

Step #10 - 0 Minutes

Step #11 - 0 Minutes

Step #12 - 0 Minutes

Step #13 - 0 Minutes

Step #14 - 20 Minutes

Step #15 - 20 Minutes

Switch next to #15 Timer to the "15 - 14" Position.

B. Initiate Module C

1. Timer #14 will operate first. However, it will now be timing Step #15 which is the screened backwash.

2. Adjust C-5 Regulator for  $140 \pm 10$  GPM.

3. Time #15 will operate next after a 3 minute time delay. But, it will be timing Step #14 which is the unscreened backwash.

4. Adjust C-5 Regulator for  $100 \pm 10$  GPM.



APR 23 1979

2106-2.2  
Revision 9  
03/21/79

- \_\_\_\_ C. If Backwash Water of Step #14 (Timer #15) is not clean, place Module C to EXTEND until it clears.
- \_\_\_\_ D. After backwash is complete and resin has settled for 10 minutes check for resin bed separation (interface) See Fig. 4.3-1 and correct resin levels per 2106-2.2 - 4.3. Then adjust resin levels as necessary. See 4.2 and 4.3 for instructions.

#### \_\_\_\_ 4.1.8 Hotwater Tank Line-Up

- \_\_\_\_ A. Insure Unit #1 has Demin. Water lined-up to Unit #2.
- \_\_\_\_ B. Open WT-V-317C (Hotwater Tank Inlet).
- \_\_\_\_ C. Open R-8, C-9 and C-12 by placing in HAND. Adjust dilution water to 32 GPM by throttling WT-V-318A.
- \_\_\_\_ D. Line-up steam to heat exchanger by opening AS-V-250, check open AS-V-251, then throttle open AS-V-252 until Hot Water Outlet of heat exchanger can be touched for only a few seconds.
  - \_\_\_\_ 1. Do not exceed 200°F on Hotwater Tank.
- \_\_\_\_ E. Adjust blend valve until temperature is 120°F  $\pm$  10°.

#### \_\_\_\_ 4.1.9 Caustic Injection

- \_\_\_\_ A. Open A-2, Interface Valve located on Ammonex Panel.
- \_\_\_\_ B. Close C-12 by placing in AUTO.
- \_\_\_\_ C. Check dilution flow at 32 GPM (Throttle WT-V-318A if necessary).
- \_\_\_\_ D. Check dilution temp at 120°F  $\pm$  10°.

2106-2.2  
Revision 9  
APR 23 1979 03/21/79

- \_\_\_\_ E. Place control switch for C-5 to the 28 GPM position. Adjust air control valve 5C inside master panel at skid, for an additional 25 GPM. Total flow should now be 57 GPM. (32 GPM dilution + 25 GPM blocking water).
- \_\_\_\_ F. Place X-1; X-2 valve to X-2 and the "A" conductivity recorder to HAND.
- \_\_\_\_ G. Place control switch for R5/6/7 in HAND. R5 and 6 open, R-7 closes.
- \_\_\_\_ H. Place control switch for WT-P-13 in HAND. Stroke on pump will be on ~90%.
- NOTE: WT-P-12 may be substituted for WT-P-13 by starting WT-P-12 from the L.A.W.T. Panel and placing WT-P-13 in OFF.
- \_\_\_\_ I. A reading of 4.0% - 5.0% on the dilute caustic conductivity recorder (Red Pen) should be observed. Adjust pump stroke as necessary.
- \_\_\_\_ J. Continue caustic injection for 45 minutes; monitoring dilution flow, blocking flow, caustic concentration and dilution temperature.
- \_\_\_\_ K. After 45 minutes have elapsed stop WT-P-13 and place control switch for R5/6/7 in AUTO; R5 and 6 will shut, R-7 will open.

\_\_\_\_ 4.1.10 Caustic Displacement

- \_\_\_\_ A. Continue as in Step 4.1.8.J. with the exception that caustic is no longer being injected. Maintain dilution flow and temperature as in Steps 4.1.8.C., D, and E.

194 259

APR 23 1979

2106-2.2  
Revision 9  
03/21/79

- \_\_\_\_ B. After 40 minutes have elapsed, place control switches for C-9 and R-8 in AUTO.

\_\_\_\_ 4.1.11 Securing Steam and Hotwater Tank

- \_\_\_\_ A. Shut AS-V-250 and AS-V-252.  
\_\_\_\_ B. Shut WT-V-317C (Hotwater Tank Inlet Valve).

\_\_\_\_ 4.1.12 Caustic Rinse

- \_\_\_\_ A. Place Control Switch for C-14 in the 120 GPM position. Adjust C-14 Regulator in panel to obtain 120  $\pm$  5 GPM.  
\_\_\_\_ B. OPEN WT-V323H (sample valve off interface piping in rear of receiving tank). OPEN 1/2 turn to get flow through tubing to sump.  
\_\_\_\_ C. Place the "B" Conductivity Recorder to HAND and the X1-X2 valve control to AUTO.  
\_\_\_\_ D. Monitor the "Receiving Tank interface conductivity" (Green Pen). When conductivity is  $< 20 \mu\text{mho}$  ( $< 0.2$  on scale) the Rinse may be terminated.  
\_\_\_\_ E. If bed doesn't rinse to  $< 20 \mu\text{mho}$  in 40 min. notify Chemistry Foreman.  
\_\_\_\_ F. Upon completion of Rinse, Place C-14 to AUTO and "B" conductivity Recorder to OFF and C-5 in AUTO.  
\_\_\_\_ G. Close A-2 Ammonex Panel.  
\_\_\_\_ H. Close WT-V323H.

\_\_\_\_ 4.1.13 Ammonex

If mini-ammonex is called for see Appendix D.

- \_\_\_\_ A. Check Ammonia Tank AM-T-6 for a positive pressure of 4-9 psi. (Tank MUST be pressurized if outside temperatures are above 75°F.)

194 260



APR 23 1979

2106-2.2  
Revision 9  
03/21/79

- \_\_\_\_\_ B. Check X-1, X-2 valves; X-2 must be OPEN.
- \_\_\_\_\_ C. Open R-11P, C-17 and A-2 by placing switches to the ON position. (These valves are located on the Ammonex Panel.)
- \_\_\_\_\_ D. Turn on an Ammonia pump AM-P-4A, B, or C by placing switch to HAND (located on Cond. Polisher Panel) and run for 10 minutes.
- \_\_\_\_\_ E. Stop Ammonia pump by placing switch to OFF.
- \_\_\_\_\_ F. Close R-11P, C-17 and A-2 by placing switches to OFF.
- \_\_\_\_\_ G. Turn on Ammonex conductivity equipment by placing meter switches to MEASURE. Turn on recorder chart drive by pulling out recorder, on-off switch is on right side. Label chart with Bed number and date.
- \_\_\_\_\_ H. Open conductivity cell isolation valves WT-V480 and WT-V471 all the way.
- \_\_\_\_\_ I. Check open WT-V-473, recycle pump suction valve.
- \_\_\_\_\_ J. Open A-1 by placing switch to ON (located on Ammonex Panel).
- \_\_\_\_\_ K. Turn on Ammonex Recycle Pump by placing switch to ON (located on Ammonex Panel).
- \_\_\_\_\_ L. Throttle Pump Discharge valve WT-V-475 to obtain a recirc. flow rate of  $90 \pm 5$  GPM on Recycle Flow Gauge.
- \_\_\_\_\_ M. After 30 minutes of recirc. both the Ammonex Hi and Ammonex Lo conductivities should be stable. The Ammonex Lo should be in the range of 300 - 500  $\mu$ mho.

APR 23 1979

2106-2.2  
Revision 9  
03/21/79

NOTE 1: If Ammonex Lo (Red Pen) is  $>500 \mu\text{mho}$  - no action required.

NOTE 2: If Ammonex Lo (Red Pen) is  $<300 \mu\text{mho}$  - Repeat 4.1.12 A-M until the 300 - 500  $\mu\text{mho}$  range has been reached. A time adjustment in Step 4.1.12.D will be necessary: 2 minutes = 100  $\mu\text{mho}$  INCREASE.

- N. Continue Ammonex recirc. until the difference (Green Pen) stops dropping and has been stable for 1 hour.
- O. Notify Chemistry to take Hi and Lo samples for Sodium Analysis. WT-V-323H and WT-V482. Acceptance criteria is that Hi and Lo Na be within .5 ppm of each other.
- P. After Sodium is inspected turn off recycle pump by placing switch to OFF.
- Q. Close A-1 by placing switch to OFF.
- R. To Rinse Bed; open C-14 and C-4 by placing switches to ON (Ammonex Panel) then adjust rinse flow to 120  $\pm$  10 GPM using C-14 Regulator. Rinse for 15 minutes.
- S. Close C-14 and C-4 by placing switches to OFF.
- T. Turn off conductivity equipment by placing meter switches and chart drive to OFF.
- U. Close conductivity cell isolation valves WT-V480 and WT-V471.

#### 4.1.14 ACID INJECTION SECTION I

##### Acid Injection and Rinse (Module D, Steps 19 and 20)

NOTE: If using Milroyal Pump see Acid Injection Section 2.

APR 23 1979

2106-2.2  
Revision 9

03/21/79

- 47
- \_\_\_\_ A. Check A-2 in OFF, X-1; X-2 in AUTO and "A" conductivity recorder in HAND.
  - \_\_\_\_ B. Check timers for Steps 16, 16A, 17 and 18 on Module D are timed out.
  - \_\_\_\_ C. Set Step 19 and 20 to:  
Step 19 - 65 Minutes  
Step 20 - 60 Minutes
  - \_\_\_\_ D. Initiate Module D.
  - \_\_\_\_ E. If acid dilution water is not 54 GPM throttle with WT-V318B.

NOTE: If dilution water is below 45 GPM Acid Pump WT-P-14 will not start.

- \_\_\_\_ 1. Stroke on acid pump will be  $\approx 60\%$ .
- \_\_\_\_ F. Open C-17 and R-12 by placing in HAND, throttle WT-V323B to 20 GPM over acid dilution water flow rate (20 GPM + 54 GPM  $\approx 74$  GPM).
- \_\_\_\_ G. A reading of 8.0% to 10.0% on the dilute acid conductivity recorder (A, Blue Pen) should be observed, if not, adjust pump stroke.
- \_\_\_\_ H. After automatic sequence has switched to Step 20 allow acid to displace for 15 minutes. Then close C-3 and R-4 by placing each in OFF, and close C-17 and R-12 by placing in AUTO.
- \_\_\_\_ I. Open C-14 to the 120 GPM position and adjust the air to obtain a rinse flow of 140 GPM  $\pm 10$  on local flow indicator.



APR 23 1979

2106-2.2  
Revision 9

03/21/79

- J. Place the "B" Conductivity Recorder in HAND.
- K. Allow bed to rinse at this rate until conductivity at receiving tank drain (Red Pen) is  $<20 \mu\text{mho}$  (2 on scale). This may involve putting step into EXTEND.
- L. After bed is  $<20 \mu\text{mho}$  readjust C-14 air regulator to  $120 \text{ GPM} \pm 10$ . Put Step 20 back into TIME. When timer is timed out put C-14 to AUTO. Place "B" conductivity recorder to OFF and place C-3 and R-4 to AUTO.

## ACID INJECTION SECTION II

### Acid Regen. Using Temporary Milroyal Pump

- A. Prior to continuing with ACID regeneration perform following valve lineup for temporary pump

		<u>Initial</u>
TF-WT-V-1	Closed	_____
TF-WT-V-2	Open	_____
TF-WT-V-3	Closed	_____
TF-WT-V-4	Open	_____
TF-WT-V-5	Open (To pressure gauge)	_____
TF-WT-V-6	Closed	_____
WT-V-314Q	Closed	_____
WT-V-314O	Open	_____
WT-V-314L	Closed	_____
WT-V-314N	Open	_____
WT-V-314M	Closed	_____

- B. Check A-2 in OFF, X-1; X-2 in AUTO and "A" conductivity recorder in Hand.
- C. Check timers for Steps 16, 16A, 17 and 18 on MODULE "D" are timed out.

APR 23 1979

2106-2.2  
Revision 9  
03/21/79

- 49
- \_\_\_\_ D. Set Step 19 to 65 minutes.  
Set Step 20 to 60 minutes.
  - \_\_\_\_ E. At polisher control panel, place WT-P-14 control switch to OFF.
  - \_\_\_\_ F. Initiate Module D.
  - \_\_\_\_ G. If acid dilution water is not 54 GPM, throttle with WT-V318B.

NOTE: If dilution water is below 45 GPM, temp Milroyal pump will not start.

- \_\_\_\_ H. Open C-17 and R-12 by placing in HAND, throttle WT-V323B to 20 GPM over acid dilution water flow rate (20 + 54  $\approx$  75 GPM).
- \_\_\_\_ I. At LAWT panel, place WT-P-11 control switch in "POL AUTO" position. This electrically aligns Milroyal to run in place of WT-P-11 which has been removed.
- \_\_\_\_ J. A reading of 8.0% to 10.0% on the dilute acid conductivity recorder (A, Blue Pen) should be observed, if not, adjust Milroyal pump stroke by using stroke adjustment knob on control panel mounted above pump (the present set up finds pressure gauge at 11 psi and stroke  $\approx$  60%).

CAUTION: Adjust pump stroke very slowly.

- \_\_\_\_ K. After automatic sequence has switched to Step 20 allow acid to displace for 15 minutes. Then close C-3 and R-4 by placing each in OFF, and close C-17 and R-12 by placing in AUTO.

4.1.16 Resin Transfer And Mix (Module F Steps 21, 21B, and 22)

- A. Check Timers:
  - Step 21 - 15 Minutes
  - Step 21A - C Minutes
  - Step 21B - 10 Minutes
  - Step 22 - 30 Minutes
- B. Initiate Module F - Check Table 2B for correct flows and valve operations.
- C. Open S-4 by placing it in HAND.
- D. As soon as Step 21B starts put Module to EXTEND and close S-7, Open S-6 (S-4 will still be open).
- E. Drain the storage tank for 5 minutes, then place S-4, S-6 and S-7 to AUTO and put Module back to TIME.
- F. Watch Resin Bed while in Step 22, when it stops moving in upper sight glass then time out Step 22.
- G. For a good transfer the Resin Level should be visible at about the center of the upper sight glass.
- H. Drain the receiving tank by placing C-4 and C-11 to HAND. When the tank is drained, place C-4 and C-11 switches to AUTO.
- I. Close SA-V238.

4.1.17 Final Rinse (Module G Steps 23 and 24)

- A. Set up module G as follows:
  - 1. Step #23 - 5 Minutes
  - Step #24 - 20 Minutes
  - 2. Place "B" Conductivity Recorder to HAND.



APR 23 1979

- \_\_\_ B. Initiate Module G.
- \_\_\_ 1. Adjust S-5 Air Regulator for 200 GPM  $\pm$  10.
- \_\_\_ C. Watch "Storage Tank drain conductivity" (Blue Pen)  
the bed should rinse in to 0.1 - 0.5  $\mu$ mho. If it  
doesn't notify Chemistry Foreman.
- \_\_\_ D. When Module G is complete place "B" conductivity  
Recorder to OFF.

You now have completed the Regeneration. Go to 4.1.4  
when ready to transfer.

#### \_\_\_ 4.2 Adding Anion and Cation To The Receiving Tank

- \_\_\_ A. Anion and Cation comes in 7 ft<sup>3</sup> drums. During the normal  
course of polisher operations it may be necessary to add  
either cation or anion.  
  
Prior to resin addition insure no resin transfer from the  
polishers or the storage tank is taking place. Have a  
temporary demineralized water supply to the resin hopper  
in the 305' elevation of the turbine building. (From  
Coagulator Building)
- \_\_\_ B. Open C-1, WTV-84 and C-4.
- \_\_\_ C. Add resin slowly to hopper with a continous sluice water  
flow to the receiving tank.
- \_\_\_ D. When addition is finished Close WT-V-84 and place C-1 and  
C-4 to CLOSE and AUTO.
- \_\_\_ E. Refill receiving tank, Open C-12 and C-14 to the 120 GPM  
position, by placing to HAND.
- \_\_\_ F. When water comes out vent Close C-12 and C-14 by placing  
to AUTO.

APR 23 1979

2106-2.2  
Revision 9  
03/21/79

\_\_\_\_ G. Go through 4.1.7 Backwash to separate new Resin.

4.3 Resin Levels And Additions

- \_\_\_\_ A. A Resin charge is made up of ~ 100 cu. ft. of Cation Resin (Amberlite 200 C) and ~ 66 cu. ft. of Anion Resin (Amberlite 900 C). Resin levels and quantities are very important for ion exchange in service and correct orientation in Receiving Tank during Regeneration.
- \_\_\_\_ B. After a Backwash the Cation (200 C) will be on the bottom of the Receiving Tank and the Anion (900 C) will be above.
- \_\_\_\_ C. The Interface (point where Cation and Anion Resins meet) must not be more than 11 inches above the bottom of the Lower Sight Glass or less than 9 inches from same point.
- \_\_\_\_ D. The amount of Cation Resin needed will have to be calculated first to adjust the interface and then the needed Anion Resin must be calculated taking into account how much space the additional Cation Resin will occupy.
- \_\_\_\_ E. The top of the Resin Bed must not be more than 10 inches above the bottom of the upper sight glass or less than 7 inches from same point.
- \_\_\_\_ F. The Receiving Tank will hold 2.0 cu. ft. of Resin per inch of vertical tank height.
- 1 inch = 2.0 cu. ft. Resin
- \_\_\_\_ G. Do not adjust Resin levels less than 3.5 cu. ft. (1/2 Drum) or 1 1/2 inches of one type of Resin.
- \_\_\_\_ H. Add Resin per 2106-2.2 - 4.2.

194 268

APR 23 1979

2106-2.2  
Revision 9  
03/21/79

53

- \_\_\_\_ L. Open C-14 to the 120 GPM position and adjust the air to obtain a rinse flow of 140 GPM  $\pm$  10 on local flow indicator.
- \_\_\_\_ M. Place the "B" Conductivity Recorder in HAND.
- \_\_\_\_ N. Allow bed to rinse at this rate until conductivity at receiving tank drain (Red Pen) is  $<20$   $\mu$ mho (2 on scale). This may involve putting step into EXTEND.
- \_\_\_\_ O. After bed is  $<20$   $\mu$ mho readjust C-14 air regulator to 120 GPM  $\pm$  10. Put Step 20 back into TIME. When timer is timed out put C-14 to AUTO. Place "B" conductivity recorder to OFF and place C-3 and R-4 to AUTO.
- \_\_\_\_ P. On LAWT panel place WT-P-11 control switch to OFF.
- \_\_\_\_ Q. Continue with regeneration cycle using Step 4.1.15 of OP 2106-2.2B.

\_\_\_\_ 4.1.15 Storage Tank Drain

- \_\_\_\_ A. Open SA-V238, Place X-1; X-2 to waste (far right).
- \_\_\_\_ B. Place S-2 to AUTO.
- \_\_\_\_ C. Place S-6 and S-1 in HAND. Both valves will OPEN.
- \_\_\_\_ D. When vessel is empty, place control switch for S-6 and S-1 in AUTO.
- \_\_\_\_ E. Place control switch for S-2 in HAND and allow tank to vent off. After tank is vented, return S-2 to AUTO.



TROUBLE SHOOTING AND HELPFUL HINTS


1. Always check valve position before starting each step.
2. When doing steps which use the Automatic Modules, always check the lineup at the back of the procedure (Table 2B) to insure that proper valves open and close.  
If they don't, check if they are in AUTO at local air switches and at panel. Also check to see that applicable valves have not been overridden at Ammonex Panel.
3. No water flow
  - a. Check that you have an open path for the water (inlet to tank and outlet from tank).
  - b. Check if water is still coming from Unit #1.
  - c. Check if 50 K tank or hotwell is being filled.
4. READ THE PROCEDURE CAREFULLY. Don't take shortcuts, follow guides indicated in procedure.
5. Acid or caustic concentration problems.
  - a. Have Chemistry take specific gravity to see if recorder and probe is working properly.
  - b. Make sure proper valves are opened (visually at valve if necessary).
  - c. Check if pump is pumping properly (listen for ball check valves slapping good and hard at both ends of stroke, if not, beat on check valves to loosen balls (not too hard though)).
  - d. Check levels of acid and caustic tanks.
6. Hotwater problems for caustic injection.
  - a. Blow down steam traps to insure steam flow is getting to heater.

52  
CCS  
APR 23 1979


2106-2.2  
Revision 9  
03/21/79

- b. Raise average temperature in hotwater tank to  $\approx 180$  before starting.
  - c. Outside water maybe too cold.
7. Transferring Resin
- a. Make sure you have water flowing, otherwise, resin will pack tightly in lines.
  - b. From polisher to receiving tank make sure you have bed swirling for the indicated 30 minutes with the air bump every 10 minutes. Be sure it swirls when air isn't on.
  - c. From Storage Tank to Polisher be sure air pressure doesn't overcome water pressure and stop water flow. (This is why we now use the fluffing air instead of the transport air to move the resin, it keeps the resin mixing.)
8. Always check that the flow rates are as required, otherwise resin loss and even internal damage might occur.
9. Hot water tank - if heater is in ON position at panel but not on, and temperature is low (less than  $80^{\circ}$ ), have electrical maintenance check fuses in breaker for heater. It has a tendency to blow them.
10. Ammonex - if conductivity doesn't come in after about 35 minutes, try again with a different ammonia pump, then go to tank and verify pump is pumping. Check valve flutter, accumulation pressure and also vent the accumulation to make sure pump is pumping. When doing this, do it slowly and be careful.
- a. If Chemist has trouble getting sample off WT-V482, isolate conductivity cell, this should force flow thru WT-V482. If this doesn't work milk rubber hose to establish a siphorn effect, this usually works. After you get the sample put the conductivity cell back in service.

Figure 4.3-1



**POOR ORIGINAL**



194 272



APR 23 1979

2106-2.2  
Revision 9  
03/21/79

TABLE 1A

SERVICE AND RESIN TRANSFER IN - REMOTE MANUAL OPERATION

STEP SEQUENCE NO.	UNIT & STEP FUNCTION	VALVES OPENED	FLOW		TIME MIN.
			WATER GPM	AIR SCFH	
1.	In Service to exhausted Polisher	M11, M12	2490		Exhausted
2.	To Recycle, Polisher	M21B, M21, M26, MC1	600		6 minutes
3.	To Service, Polisher	M21B, M21, M22	2490		To sub- quality
4.	Out of Service, Polisher	All valves closed			
5.	Relieve Pressure, Polisher	M13			
6a.	Set Up Receiving Tank	C12, C4, X1, C1			
6b.	Resin Transfer to Receiving Tank	See 4.1.4 of Procedure			
7.	Drain Polisher	M13, M16, MC1			
8.	Resin Transfer to Polisher	See 4.1.5 of Procedure			
9.	Flush Storage Tank & Refill Polisher to Standby Condition	M13, M15, S8, S11, S1	75		15

TABLE 2B

APR 23 1979

2106-2.2  
Revision 9  
03/21/79

MODULE	STEP	FUNCTION	TIME (MINS)	OPEN	CLOSE	FLOW (GPM)	REMARKS
C	14 (15 Timer)	Slow Backwash (Remove Fines)	20	C5 C13 X1	X2	100	If fines are not removed within 20 minutes, place extend cycle step control switch in "Extend" and allow backwash to continue until fines are removed. Then place switch back to "TIME" position and allow timer to Time Out. <u>NOTE:</u> Be carefull not to exceed 100 GPM in order to prevent resin loss as Outlet for this backwash is un-screened.
C	15 (14 Timer)	Fast Backwash	20	C5 C12 X1	X2	140	Resin separation takes place during this step. Anion on top, cation on bottom. Vibrator energized to prevent resin from blocking flow at screened outlet.
		Inject Caustic <u>NOTE:</u> This Step in Manual. Follow 4.1.8	45	C5 C9 R5 R6 R8 X2 A2	R7     X1	Dilution 32.0 Blocking 25.0	Caustic concentration: 4% - 5%, Use dilute caustic conductivity recorder (Red Pen). Reading should be 4.0 - 5.0. Dilution Temp - 120°F ± 10.
		Displace Caustic <u>NOTE:</u> This Step is manual. Follow 4.1.9	40	C5 C9 R8 R7 X2 A2	R5 R6   X1	Dilution 32.0 Blocking 25.0	Dilution Temperature 120°F. X1 and X2 will cycle when waste outlet conductivity reaches 50 µmho (Green Pen on 'A' conductivity recorder). If cycling is excessive place control switch for X1 and X2 in the middle position. This will keep X2 open and X1 Closed. Leave this way until conductivity is below 50 µmho and then return switch to "AUTO" X1 should stay open now and X2 should stay Closed.

194 274

APR 23 1979

TABLE 2B

MODULE	STEP	FUNCTION	TIME (MINS)	OPEN	CLOSE	FLOW (GPM)	REMARKS
		Rinse Caustic <u>NOTE:</u> This Step is manual. Follow 4.2.11	40	C14 X1 A2 WT-V323H	X2	120	Normal rinse time is 25 minutes. Use Green Pen on 'B' Conductivity Recorder.
D	19	Inject Acid	65	R1 R2 R4 C3 C4 X2 R-12 C-17	R3 A2    X1	Dilution 54 GPM Blocking 20 GPM	Acid Concentration: 5%, Use Dilute acid conductivity recorder (Blue Pen). Reading should be 8.0 - 10.0 Adjust WT-P-14 stroke as necessary to obtain correct concentration. If recorder is not working have Chem Tech sample specific gravity and adjust for 1.045- 1.059. Throttle WT-V-318B to obtain 54 GPM Dilution Flow as read on Rotometer (F1-3) next to storage tank. WT-P-14 will automaticall start at beginning and stop at end.
D	20	Displace Acid	60	R-12 R-14 C-14 R4 C3 C4 X2	R1 R2 A2  X1	First 15 Mins. 74 Remainder 130-140	Refer to 4.1.13 H and 4.1.13 I.
H	25	Air Lance Receiving Tank	30	C5 C6 C12		25 GPM 145 SCFM	Mechanical Cleaning (Scrubbing). Screen Plugging See 4.1.6.C.2
H	26	Backwash Vibrate Screen	0	C5 C12		0	Backwash Impurities removed from Air Lance

194  
275



TABLE 2B

APR 23 1979

MODULE	STEP	FUNCTION	TIME (MINS)	OPEN	CLOSE	FLOW (GPM)	REMARKS
II	27	Backwash Screen	5	C16		70	Unit will automatically shift from backflush to backwash after 5 minutes.
				C4			
				X1	X2		
F	21	Transfer Resin to Storage Tank	15	C5		100	Be careful not to exceed 100 GPM during unscreened backwash in order to prevent loss of resin
				C13			
				X1	X2		
F	21	Transfer Resin to Storage Tank	15	S4		Sluice 75	Open S-4 Manually
				S6			
				C11			
F	21B	Air Mix	10	C8		145 SCFM	Mix anion and cation resins
				C7			
				X1	X2		
F	21A	Partial Refill Storage Tank	0	S11		75	
				S2			
F	22	Air Mix Drain Storage Tank	30	S2		145 SCFM	
				S4			
				S7			
G	23	Refill Storage Tank	5	X1	X2	200	Fill for 5 minutes or until water issues from vent.
				S2			
				S5			
G	24	Final Rinse	20	S5		200	Final conductivity rinse to remove trace chemicals to .1 - .5 $\mu$ mho
				S6			
				X1	X2		

194 276

APR 23 1979

CHEMISTRY DATA SHEET

\_\_\_\_\_ Bed Letter  
\_\_\_\_\_ Vessel Removed From \_\_\_\_\_ Date/Time \_\_\_\_\_  
\_\_\_\_\_ Date/Time In Service  
\_\_\_\_\_ Date/Time Out of Service  
\_\_\_\_\_ How Many Mechanical Clean Cycles?  
\_\_\_\_\_ Caustic Concentration Reading  
\_\_\_\_\_ Caustic Rinse Conductivity  
\_\_\_\_\_ Ammonex: Low Conductivity Reading  
\_\_\_\_\_ Ammonex: High Sodium Result  
\_\_\_\_\_ Ammonex: Low Sodium Result  
\_\_\_\_\_ Ammonex: Time to Complete  
\_\_\_\_\_ Acid Concentration Reading  
\_\_\_\_\_ Acid Rinse Conductivity  
\_\_\_\_\_ Final Rinse Conductivity

Resin:

\_\_\_\_\_ Added Amberlite 200 C-H (How Much?)  
\_\_\_\_\_ Added Amberlite 900 C-OH (How Much?)

Please return this Data Sheet to OPERATIONS ENGINEER.

Initial _____	_____ Signature
Initial _____	_____ Signature
Initial _____	_____ Signature
Initial _____	_____ Signature
Initial _____	_____ Signature
Initial _____	_____ Signature

62  
CAL  
3 1979

APR 23 1979

1000

194 278



63  
APR 23 1979

2106-2.2  
Revision 9  
03/21/79

# APPENDIX C

## Procedure For Short Regen. (Acid Only)

1. Do Step 4.1.6 (A - E) Mechanical clean.
2. Mini Ammonex is next.
  - a. Do Step 4.1.13 except run pump for 20 minutes instead of 10 minutes.
  - b. Do all steps up thru "L".
  - c. Terminate recycle as soon as low conductivity (Red Pen) gets to 200 - 300 umhos.
  - d. Go to Step "P" and complete remainder of Section 4.1.13.
3. Do Step 4.1.7 (complete thru D) skip to 4.1.14 next.
4. Do regular acid Step 4.1.14.
5. Complete remainder of Regen. in order.

APPENDIX D

MINI AMMONEX PROCEDURE

1. Complete Regen. up thru 4.1.6 MECH CLEAN.
2. Then go to Step 4.1.13 of procedure.
3. Complete Steps A + L as written except on Step D - run the pump for 20 minutes instead of 10 minutes.
4. Terminate the recycle as soon as the red pen reaches 300 - No sampling is required by the Chemistry Dept. during the Mini Ammonex.
5. Go to Step 4.1.13 - P and complete the remainder of 4.1.13.
6. Go back to Step 4.1.7 - Backwash - and do the remainder of the regeneration from that point on as written.

TMI DOCUMENTS

DOCUMENT NO: TM-024

COPY MADE ON 5/2/79 OF DOCUMENT PROVIDED BY  
METROPOLITAN EDISON COMPANY.

WRM  
Wilda R. Mullinix, NRC

7906140280

194 217