

AP 1G01  
Figure 1G01-8

Three Mile Island Nuclear Station  
Special Operating Procedure

SIDE 1  
SOP No. 7-110  
(From SOP Log Index)

NOTE: Instructions and guidelines in AP 1G01 must be followed when completing this form.

Unit No. TWO  
Date ~~4/27/79~~  
4/29/79

1. Title Establishing Water/Water Heat Removal Mode on the "B" OTSG

2. Purpose (include purpose of SOP)  
To convert the "B" steam generator from an isolated secondary side condition to a heat removal mode with the secondary side filled with water and rejecting heat to the main condenser.

3. Attach procedure to this form written according to the following format.  
A. Limitations and Precautions  
1. Nuclear Safety  
2. Environmental Safety  
3. Personnel Safety  
4. Equipment Protection  
B. Prerequisites  
C. Procedure

4. Generated by TSPG Date ~~4/27/79~~  
4/29/79

Duration of SOP -- Shall be no longer than 90 days from the effective date of the SOP or (a) or (b) below -- whichever occurs first.

- (a) SOP will be cancelled by incorporation into existing or new permanent procedure submitted by \_\_\_\_\_
- (b) SOP is not valid after \_\_\_\_\_   
(fill in circumstances which will result in SOP being cancelled)

- 6. (a) Is the procedure Nuclear Safety Related?  
If "yes", complete Nuclear Safety Evaluation. (Side 2 of this Form) . . . . . Yes  No
- (b) Does the procedure affect Environmental Protection?  
If "yes", complete Environmental Evaluation. (Side 2 of this Form) . . . . . Yes  No
- (c) Does the procedure affect radiation exposure to personnel? . . . . . Yes  No

NOTE: If all answers are "no", the change may be approved by the Shift Supervisor. If any questions are answered "yes", the change must be approved by the Unit Superintendent.

7. Review and Approval  
Approved - Shift Supervisor \_\_\_\_\_ Date \_\_\_\_\_  
Reviewed - List members of PORC contacted \_\_\_\_\_ Date \_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
Approved - Unit Superintendent \_\_\_\_\_ Date \_\_\_\_\_

8. SOP is Cancelled  
\_\_\_\_\_  
Shift Supervisor/Shift Foreman Date

ESTABLISHING WATER/WATER HEAT REMOVAL  
MODE ON THE "B" OTSG

1.0 PURPOSE

- 1.1 To convert the "B" steam generator from an isolated secondary side condition to a heat removal mode with the secondary side filled with water and rejecting heat to the main condenser.

The overall sequence of operations is:

- Fill the secondary side of OTSG "B" with water, overflowing into the Main Steam and bypass line.
- Establish feedwater flow to the main condenser through the turbine bypass lines.

2.0 REFERENCES

- 2.1 Main and Reheat Steam System; Flow Diagram, 2002.  
2.2 Feedwater and Condensate; Flow Diagram; 2005.  
2.3 Feedwater Heater Drains, Flow Diagram 2555

3.0 LIMITATIONS AND PRECAUTIONS

- 3.1 Determine the need or requirements for lube oil to the main feed pump and turbine during windmilling.
- 3.2 Establish and maintain optimum condensate pump flow for indefinite operation. If necessary, use the condensate booster pump(s) recirculation lines to the condenser (CO-V35A, B, and C and/or their associated manual isolation valves, CO-V36A, B and C) and/or either or both S/G. F. W. pump recirculation lines to the condenser (FW-V12A and FW-V12B).
- 3.3 Monitor condensate pump suction strainer delta P periodically.
- 3.4 While filling the B S/G or during any operations involving feedwater flow changes to the B S/G, adjustments of the steaming rate from the A S/G shall be made as necessary to maintain a near constant RCS temperature.
- 3.5 The bulk water/steam temperature in the steam generator should be within 60°F of the steam generator wall temperature to avoid creating tube stresses. (Temperature limit of concern is the  $T$  between average S/G shell temperature as read on computer, and RCS  $T_{ave}$ ).

- 3.6 The auxiliary feed lines are assumed dry by this procedure. If full, then the time required will be reduced to complete fill. Fill completion will be indicated by increasing steam generator pressure on installed gauge.
- 3.7 Sufficient condensate/condensate makeup is available to complete this procedure.
- 3.8 Because the B S/G contains contaminated water, during the performance of this procedure and until the entire secondary system is returned to acceptable activity levels, normal Health Physics practices for contaminated systems shall be observed.

4.0 PREREQUISITES

4.1 Initial conditions

4.1.1 Primary

- a. RCS in natural circulation
- b. The primary system temperature is being maintained as low as practical by steaming heat removal methods on steam generator "A"

4.1.2 Secondary

- a. The following valves associated with the Feedwater System are closed:

- FW Control valve isolation valves: FW-V14B
- FW control valve: FW-V17B
- FW startup line isolations: FW-V30B
- S/G Emergency FW isolation valves: FW-V19B
- FW startup flow control valve: FW-V26B
- FW control valve warm-up bypass isolation: EF-V12B
- FW heater 3B isolation valves: EF-V33B
- FW control valve warm-up bypass isolation: FW-V25B
- FW heater 3B isolation valves: FW-V66B

- b. The following valves associated with the Feedwater system are open:

- FW heater 3B isolation valves: FW-V9B
- FW heater 3B isolation valves: FW-V13B

- FW pump B suction & discharge isolation valves:

CO-V52B

FW-V8B

\_\_\_\_\_  
\_\_\_\_\_

- FW pumps A&B common suction isolation:

CO-V55

\_\_\_\_\_

c. The following valves associated with the Main and Reheat Steam system are closed:

- Main steam isolation valves:

MS-V4B

MS-V7B

\_\_\_\_\_  
\_\_\_\_\_

- Turbine Bypass isolation valve:

MS-V15B

\_\_\_\_\_

- Turbine bypass control and isolation valves:

MS-V23B

MS-V24B

MS-V25B

MS-V26B

\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

- Moisture Separator-Reheater Isolation Valves:

MS-V32A

MS-V33A

MS-V32B

MS-V33B

\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

- Emergency S/G FWP isolation valves:

MS-V11B

MS-V207

\_\_\_\_\_  
\_\_\_\_\_

- Main FWP (FW-U1A) Steam Inlet isolation and stop valves:

MS-V21B

MS-V49A

\_\_\_\_\_  
\_\_\_\_\_

- Atmospheric Dump Valve Isolations:

MS-V1B

MS-V2B

\_\_\_\_\_  
\_\_\_\_\_

D. Isolate the following turbine bypass line steam traps:

MS-U31B

MS-U34B

MS-U35B

\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

- e. Condenser vacuum\* is established and the vacuum pump(s) discharge is through a filtration system
- 

\*Maintaining condenser vacuum throughout the filling and recirculation modes herein is desirable for two reasons:

- It will facilitate deaeration of the feedwater and minimize build-up of a noncondensable gas bubble in the OTSG.
- It will aid in cooling feedwater that returns from the OTSG.

#### 4.2 MODIFICATIONS

4.2.1 All automatic transfers from the Bypass Control Valves to the Atmospheric Dump Valves have been defeated:

---

4.2.2 All necessary modifications to the feed and steam system piping (i.e., isolable flange connections) to facilitate future installation of the proposed closed cooling loop are installed.

---

#### 5.0 Special Equipment

5.1 None

#### 6.0 Method

##### 6.1 Filling Secondary Side of Generator with Water

6.1.1 Water source to be used for fill operations is available (approx. 28,000 gallons).

---

NOTE: It is expected that additional amounts of hydrazine will be required to provide and maintain proper chemistry in the "B" OTSG. Provide chemical additions as directed by the Chemistry Department.

6.1.2 Open the FW startup flow control valve isolation valve:

FW-V19B

---

NOTE: It is estimated that full flow through FW-V-66B will be a maximum of 80 gpm with valve full open. It is desired to limit flow to approximately 50 gpm.

NOTE: If alternate S/G level indication is available, monitor S/G level increase and adjust FW-V66B as necessary to obtain 1" per minute S/G level increase. (This is approximately equal to 42 gpm)

- 6.1.3 Throttle open the FW control valve warmup bypass isolation, FW-V66B, to approximately 1/2 to 3/4 open.

FW-V66B throttled \_\_\_\_\_

- 6.1.4 Open the turbine bypass line isolation:

MS-V15B \_\_\_\_\_

NOTE: As the S/G approaches a solid condition, S/G pressure will increase.

- 6.1.5 When the S/G and associated steam lines indicate being solid, as observed by the local pressure gauge or steam line pressure readings off computer point 474, perform the following:

- a. Throttle open the turbine bypass control isolation: MS-V23B

MS-V23B throttled open \_\_\_\_\_

CAUTION: During operations involving flow changes through MS-V25B an operator should be stationed at these valves to report any valve cavitation to the control room.


NOTE: The attached curve (Figure 1) is provided as guidance to prevent valve cavitation.

- b. Throttle open the turbine bypass control valve MS-V25B, maintaining 10 to 20 psi steam line/S/G pressure indication

\_\_\_\_\_

- 6.1.6 When it has been verified that the "B" OTSG is providing heat removal, begin transferring load to the "B" OTSG by closing MS-V26A or MS-V25A slowly and opening MS-V25B as necessary to maintain RCS temperature. When MS-V26A and MS-V25A are completely closed, the "A" steam generator is isolated and all heat removal is being accomplished by the "B" steam generator.

\_\_\_\_\_



NOTE:

Allowable flow region is below each curve for the corresponding inlet pressure  $P_i$ .

calc. file  
33-1100440-0

100' FOR TRUE ELEVATION  
 100' FOR TRUE ELEVATION  
 EL. 629.25  
 EL. 625.25  
 EL. 603.129

*Handwritten signature*




FIGURE 2

MPR Assoc  
 TMI-2